

PRODUCT SPEC SHEET
PRODUCT KEY: ST6C SERIES

PHONE: 01757 289067
EMAIL: INFO@SHELTERIT.CO.UK
WEBSITE: WWW.SHELTERIT.CO.UK



PRODUCT SPEC SHEET

PRODUCT KEY: ST6C SERIES

PHONE: 01757 289067
 EMAIL: INFO@SHELTERIT.CO.UK
 WEBSITE: WWW.SHELTERIT.CO.UK

WIDTH	610cm (6.1m or 20ft)
HEIGHT	180cm (Peak) - 439cm (On std. container)
WIDTH BETWEEN CONTAINERS	585cm (5.85m)
ARCH SPACINGS	150cm approx. (Centre to centre)
FRAME SPEC	Hot-dip Galvanised Steel. Main steel profile 48 x 1.5mm Steel Arch Tubing
FRAME BRACING	Steel support wind bracing in the end bays
FABRIC	Heavy duty 610g/m ² PVC Cover
FABRIC DETAILS	Tensile Strength (Grab) (BS EN ISO 13934-2:2014) Warp 180Kg - Weft 140Kg Tear Strength by Falling Pendulum. Apparatus (BS EN ISO 13937-1:2000) Tear of Warp Threads >6500g - Tear of Weft Threads 6380g Meets Solar UV Protective Properties for Textile Material (EN 13758-1:2001+A1:2006)
GABEL END PANEL OPTIONS	Full Gable Panel with 1No. Rope-up Door. W 300cm x H 300cm (accessible height). 1No. personnel access, roll-up door opening. W 90cm x H 210cm. Half Gable Panel (Netted or PVC)
COLOURS ¹	White (RAL 9003) Grey (RAL 7037) Green (RAL 6006)
ANCHORING & FIXING	Shipping Containers - Base rail and container clamping system as standard. Can be welded. Concrete Blocks - Base rail requires drilling and fixing with M16 Expansion Bolts (Extra Cost) We only recommended that the canopy be installed on sites with stable and level ground.
SHIPPING WEIGHT & SIZES ²	ST6C-6 - 345 KG 1No. W 224cm x L 110cm x H 28cm ST6C-12 - 565 KG 1No. W 224cm x L 110cm x H 42cm ST6C-18 - 785 KG 1No. W 224cm x L 110cm x H 56cm
INSTALLATION TIME (3 PERSONS—DIY)	2-3 DAYS
RECOMMENDED EQUIPMENT	Offloading: Forklift Installation: We use a 9m telehandler and a 9.8m scissor-lift.
EXPECTED LIFE SPAN ³	Galvanised Steel Frame- 10+ Years 610g/m ² PVC Cover - 5+ Years
WARRANTY ⁴	1 year on all components

¹ RAL numbers are as close an estimate as could be made, actual colour may vary slightly screen to screen.

² Shipping weight is approximate to the most recent stock check completed.

³ Life span is according to good practice and fair conditions. The PVC will require some maintenance i.e. tensioning the ratchet straps every 6 months or more to keep the fabric taut.

⁴ Warranty covers manufacturing defects only. Any damage caused by environmental conditions whilst in the box or whilst being installed or during excessive wind or snow load is not covered.